

**SPECIAL SPECIFICATION**

**SECTION 02511S**

**ASPHALT CONCRETE PAVEMENT**

1.01 PART 1 GENERAL

1.02 DESCRIPTION OF WORK

- A. This section shall apply to the materials, workmanship, recycle reuse, and operations required for the installation of asphalt concrete pavement. The scope includes asphalt paving for, roadways, parking, pedestrian ways, cart paths and other surfaces, where shown on the drawings.

1.03 REFERENCES

- A. All work shall be done in compliance with Sections 112, 113, 116 and 336 of the latest version of the City of Albuquerque – Standard Specifications for Public Works Construction (with exceptions below)
- B. Exceptions:
1. All work shall be paid for on a lump sum basis, as given in the contract documents. The measurement and Payment section of Specification Sections 112, 113, 116 and 336 shall be deleted.
  2. In accordance with the City of Albuquerque Materials and Testing Laboratory Section July 17, 2002, acceptance letter of the 2002 Asphalt Concrete Job Mix Formula Submittal (June 12, 2002; Code 541.02/551.02) by LAFARGE Southwest, Inc, the job mix formula shall be “Type B” residential design, with 1-inch maximum size aggregate, composed of five aggregates including a minimum of 15% recycled asphalt concrete, natural sand, Koch 60-70 Penn asphalt binder, and Perma Tac liquid anti-strip. Reference Table 116.F of the COA Standard Specifications for design development based on a 50 blows Marshall method and 4 inch diameter mold.

END OF SECTION