

# SANDIA REPORT

Printed January 22, 2025



Sandia  
National  
Laboratories

## Sierra/SD – User's Guide for NasGen – 5.22

Sierra Structural Dynamics Development Team

Prepared by  
Sandia National Laboratories  
Albuquerque, New Mexico 87185  
Livermore, California 94550

Issued by Sandia National Laboratories, operated for the United States Department of Energy by National Technology & Engineering Solutions of Sandia, LLC.

**NOTICE:** This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, make any warranty, express or implied, or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represent that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government, any agency thereof, or any of their contractors or subcontractors. The views and opinions expressed herein do not necessarily state or reflect those of the United States Government, any agency thereof, or any of their contractors.

Printed in the United States of America. This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from

U.S. Department of Energy  
Office of Scientific and Technical Information  
P.O. Box 62  
Oak Ridge, TN 37831

Telephone: (865) 576-8401  
Facsimile: (865) 576-5728  
E-Mail: reports@osti.gov  
Online ordering: <http://www.osti.gov/scitech>

Available to the public from

U.S. Department of Commerce  
National Technical Information Service  
5301 Shawnee Road  
Alexandria, VA 22312

Telephone: (800) 553-6847  
Facsimile: (703) 605-6900  
E-Mail: orders@ntis.gov  
Online order: <https://classic.ntis.gov/help/order-methods>



## **ABSTRACT**

NasGen provides a path for migration of structural models from Nastran bulk data format (BDF) into both an Exodus mesh file and an ASCII input file for Sierra Structural Dynamics (Salinas) and Solid Mechanics (Adagio). Many tools at Sandia National Labs (SNL) use the Exodus format. This document describes capabilities and limitations of the NasGen translation software.

This page left blank

# CONTENTS

|   |           |
|---|-----------|
| <b>1. Introduction</b>                                    | <b>13</b> |
| 1.1. NasGen Usage .....                                   | 13        |
| 1.1.1. Options .....                                      | 13        |
| <b>2. NasGen Translation</b>                              | <b>15</b> |
| 2.1. Node and Element Numbering .....                     | 15        |
| 2.2. Block Numbering .....                                | 15        |
| 2.2.1. Block Names .....                                  | 17        |
| 2.3. Nodeset Numbering .....                              | 17        |
| 2.4. Sideset Numbering .....                              | 18        |
| 2.5. Parameters .....                                     | 18        |
| 2.6. Functions .....                                      | 18        |
| 2.7. Ground .....   | 18        |
| 2.8. Case Control .....                                   | 19        |
| 2.9. Element Translation Table .....                      | 19        |
| 2.9.1. Property Cards (PCARDs) .....                      | 22        |
| 2.9.2. Rigid Pseudo Element .....                         | 23        |
| 2.10. Recognized BDF cards .....                          | 24        |
| 2.10.1. Additional Salinas BDF Card Support Details ..... | 25        |
| <b>3. NasGen Support</b>                                  | <b>27</b> |
| 3.1. Known Deficiencies .....                             | 27        |
| 3.2. Support .....  | 28        |
| 3.3. Pedigree .....                                       | 28        |
| <b>Bibliography</b>                                       | <b>29</b> |
| <b>Distribution</b>                                       | <b>30</b> |

This page intentionally left blank.

## **LIST OF FIGURES**

This page intentionally left blank.

## LIST OF TABLES

|  |    |
|--|----|
| Table 2-1. Block Numbering .....                       | 16 |
| Table 2-2. NASTRAN/Exodus Translation.....             | 20 |
| Table 2-3. NASTRAN/Salinas Element Support.....        | 20 |
| Table 2-4. NASTRAN/Presto Element Support.....         | 21 |
| Table 2-5. <b>PCARD Translation for Salinas.</b> ..... | 22 |
| Table 2-6. <b>PCARD Translation for Presto.</b> .....  | 22 |

This page intentionally left blank.

## Acknowledgments

The **Sierra/SD** software package is the collective effort of many individuals and teams. A core Sandia National Laboratories based **Sierra/SD** development team is responsible for maintenance of documentation, testing, and support of code capabilities. This team includes Dagny Beale, Gregory Bunting, Nathan Crane, David Day, Clark Dohrmann, Payton Lindsay, Justin Pepe, and Julia Plews.

The **Sierra/SD** team also works closely with the Sierra Inverse and Plato teams to jointly enhance and maintain several capabilities. This includes contributions from Wilkins Aquino, Mark Chen, Brett Clark, Sean Hardesty, Cameron McCormick, Clay Sanders, Chandler Smith, Adam Sokolow, Benjamin Treweek, Timothy Walsh, and Ray Wildman.

The **Sierra/SD** team works closely with other Sierra teams on core libraries and shared tools. This includes the DevOps, Sierra Toolkit, Solid Mechanics, Fluid Thermal Teams. Additionally, analysts regularly provide code capabilities as well as help review and verify code capabilities, testing, and documentation. Other individuals not already mentioned directly contributing to the **Sierra/SD** documentation, testing, and code base during the last year include Frank Beckwith, Simon Bignold, Samuel Browne, Gabriel de Frias, Scott Gampert, David Glaze, Mark Hamilton, Jacob Healy, Andrew Kimler, Dong Lee, Mario LoPrinzi, Kevin Manktelow, Mark Thomas Merewether, Scott Miller, Matthew Mosby, Tony Nguyen, Devin OConnor, Tolu Okusanya, Krishen Parmar, Malachi Phillips, Kendall Pierson, Thomas Ransegna, Timothy Shelton, Greg Sjaardema, Yaroslav Vasyliv, Johnathan Vo, and Alan Williams.

Historically dozens of other Sandia staff, students, and external collaborators have also contributed to the **Sierra/SD** product and its documentation.

Many other individuals groups have contributed either directly or indirectly to the success of the **Sierra/SD** product. These include but are not limited to;

- Garth Reese implemented the original **Sierra/SD** code base. He served as principal investigator and product owner for **Sierra/SD** for over twenty years. His efforts and contributions led to much of the current success of **Sierra/SD**.
- The ASC program at the DOE which funded the initial **Sierra/SD** (Salinas) development as well as the ASC program which still provides the bulk of ongoing development support.
- Line managers at Sandia Labs who supported this effort. Special recognition is extended to David Martinez who helped establish the effort.
- Charbel Farhat and the University of Colorado at Boulder. They have provided incredible support in the area of finite elements, and especially in development of linear solvers.
- Carlos Felippa of U. Colorado at Boulder. His consultation has been invaluable, and includes the summer of 2001 where he visited at Sandia and developed the Hexshell element for us.
- Danny Sorensen, Rich Lehoucq and other developers of ARPACK, which is used for eigenvalue problems.

- Esmond Ng who wrote *sparspak* for us. This sparse solver package is responsible for much of the performance in **Sierra/SD** linear solvers.
- The *metis* team at the University of Minnesota. *Metis* is an important part of the graph partitioning schemes used by several of our linear solvers. These are copyright 1997 from the University of Minnesota.
- Padma Raghaven for development of a parallel direct solver that is a part of the linear solvers.
- The developers of the SuperLU Dist parallel sparse direct linear solver. It is used through GDSW for a variety of problems.
- Leszek Demkowicz at the University of Texas at Austin who provided the HP3D<sup>2</sup> library and has worked with the **Sierra/SD** team on several initiatives. The HP3D library is used to calculate shape functions for higher order elements.

This work was supported by the Laboratory Directed Research and Development (LDRD) program.

# 1. INTRODUCTION

NasGen provides a path for migration of structural models from NASTRAN bulk data format (BDF) into both an Exodus mesh file and an ASCII input file for Sierra Structural Dynamics (Salinas) and Solid Mechanics (Presto). Many tools at Sandia National Labs use the Exodus format. NasGen was written specifically for Salinas and Presto but should be usable with a number of these packages. *However, if the translation of a NASTRAN card type to Exodus, Salinas, or Presto files is not discussed in this document then that translation is either non-existent or not verified for use.*

## 1.1. NasGen Usage

Nasgen is a preprocessor tool for generation of the geometry files distributed with Sierra Mechanics Applications. Nasgen translates most of the NASTRAN bulk data file constructs to a geometry file format, Exodus, that works with the Sierra Mechanics Applications.

`nasgen [options] example.bdf example.exo`

The `example.bdf` file is a NASTRAN bulk data deck, and the `example.exo` file is the resulting Exodus file.

### 1.1.1. Options

- S** Outputs a Salinas input file. The file is a text description of the contents of the Exodus file which can be used as a starting point to run Salinas (structural dynamics). The file name of the Salinas input is identical to the Exodus file name, with the “.inp” extension.
- P** Outputs a Presto input file. This text file can be used as a starting point to run Presto (solid mechanics). The file name of the Presto input is identical to the Exodus file name, with the “.i” extension. The output Exodus file is sensitive to this option if rigid elements are specified in NASTRAN. See Sections 2.2 and 2.9.2 for more details.
- N** Outputs a Presto input file (with auxiliary input files) that can be used as a starting point to run a coupled Presto-NEMO analysis.
- i** `input_nastran` Specify the file to read input from.
- o** `output_exodus` Specify the Exodus file to receive the data.

- i4** Instructs the program to write Exodus files in a format so that floating-point data is written in 4 bytes. This may result in a loss of accuracy. (Note: do NOT put a space between the characters, i.e. '-i 4' will generate an error).
- u** Generates a log file of the cards NOT referenced in the translation process. The file name of the log file is identical to the Exodus file name, with the ".log" extension.
- e** Echo all cards in the input bulk data deck to the log file. Note that this turns off the "-u" option. Cards are parsed and written to the log file. This is useful primarily for debugging.
- n** Establishes Navy specific translation options. For Salinas and if "-P" is not specified, this includes defaulting to the Nbeam and some specialization for mount elements.
- rbe2blk** Creates a new exodus element block for each RBE2 element in the NASTRAN input. This option is not compatible with Presto output "-P". Without this option, the RBE2 elements are put in the same block as RBARs.
- q** "Quiet" running. Only warnings are output. No informational messages are printed.
- d** "Debug" running. All debugging output is provided. When -d is specified, -q is ignored.

Note: while the options may occur in any order, the options must all occur *before* the input NASTRAN or output Exodus file is specified, i.e. they must be specified last on the command line unless the -i and -o flags are used.

## 2. NASGEN TRANSLATION

### 2.1. Node and Element Numbering

The Exodus format uses an implied node numbering of  $1:N$ , where  $N$  is the number of nodes (or GRID points) in the model. Exodus also supports a node number map. NasGen converts existing node numbering into the implicit node numbering of Exodus and provides the appropriate map. However, most tools for manipulation of Exodus files ignore the map. For example, `blot`, `p3/exodus`, and `ensight7` all ignore the node number map in output of the results data. In addition, it is common to use SEACAS tools such as `gjoin` to combine and manipulate multiple Exodus files. These processes destroy the node map.

It is therefore often advantageous (but not required) to renumber the GRID data before translation. This provides the clearest path from post processed node numbers to the original geometry. Additional methods to keep track of specific nodes in the FE model are discussed in Section [2.3](#).

The Exodus format also implicitly numbers elements. An element number map is provided back to the original element numbering from the Exodus file. Since element numbering in Exodus files is implicit by block, it is next to impossible to force a preprocessor to renumber consistent with Exodus numbering. However, it is advantageous to keep the element number range relatively small.

The element number map is used within NasGen to properly assign sideset type loads to Exodus elements. Memory for this reverse map is allocated based on the maximum difference of element numbers, i.e. an array of length  $(\text{max\_id}-\text{min\_id})$  is allocated to do this reverse map. If there are no sidesets in the model, the reverse map will not be constructed.

### 2.2. Block Numbering

Blocks in an Exodus file correspond loosely to NASTRAN properties. However, Exodus element blocks require that all elements in a block have the same element topology. Thus, a collection of CTRIA3 and CQUAD4 elements could share a single NASTRAN property card but would require at least two Exodus blocks.

Block numbering in NasGen is based on the original NASTRAN property PID. The PID is multiplied by 10, and an integer added to ensure uniqueness. The integers are shown for solid and shell elements in the Table [2-1](#). Note that we do NOT translate elements with other numbers of nodes, e.g. there is no translation of a hex element with 15 nodes.

**Table 2-1.** – Block Numbering.

| Element     | # nodes | Increment | Comment                   |
|-------------|---------|-----------|---------------------------|
| CHEXA       | 8       | 0         |                           |
| CHEXA       | 20      | 1         |                           |
| CPENTA      | 6       | 2         |                           |
| CPENTA      | 15      | 3         |                           |
| CTETRA      | 4       | 4         |                           |
| CTETRA      | 10      | 5         |                           |
| CTRIA3      | 3       | 0         |                           |
| CTRIA6      | 6       | 1         |                           |
| CQUAD4      | 4       | 2         |                           |
| CQUAD8      | 8       | 3         |                           |
| CBAR        | 2       | 0         |                           |
| CBEAM       | 2       | 0         | Equiv to bar              |
| CDAMP       | 2       | 0         | attributes not translated |
| CBUSH       | 2       | 0         |                           |
| CGAP        | 2       | 0         | attributes not translated |
| CELAS2      | 2       | 0         |                           |
| CROD        | 2       | 0         |                           |
| CONM2       | 1       | 7         | see comments              |
| Rigid Links | 2+      |           | see comments              |

Concentrated masses are treated differently from all other elements. All CONM2 are in block 17, and the mass properties are written as attributes to the Exodus file.

Rigid links have limited support. The RBE1 element is recognized, but is not translated. All RROD, RTRPLT and RBAR elements are put into the same element block. Within the block, each link of the element is defined as a two node Exodus “BEAM-R” element. Block IDs for rigid elements start immediately above all other block IDs and are incremented by one. Each element within the block is assigned an attribute identifying its source element. In addition, two attributes identify the active degrees of freedom in the element. See section [2.9.2.1](#)).

In Salinas, RBE3 elements are assigned a unique block ID, one for each RBE3. If the -rbe2blk option is specified, each RBE2 may be assigned to a unique block (as for RBE3). By default, the constraints for the RBE2 are added to the block with RBAR elements.

For Presto all RBAR, RROD, RTRPLT and fully constrained RBE2 elements are translated together. In Presto partially constrained RBE2s are converted into MPCs similar to RBE3s. In NasGen these NASTRAN elements are sorted to determine which are connected into rigid bodies but are always written to a single element block. The individual rigid bodies are indicated by an attribute written on the rigid Exodus elements, which Presto can read and use to separate rigid bodies.

### **2.2.1. Block Names**

NASTRAN contains only integers to describe the different material blocks. To facilitate block identification as names in the Exodus format, the nasgen translator can sometimes read comments associated with the NASTRAN property card. This capability is enabled with the navy option (-n on the command line), and has been exercised only for FEMAP output.

## **2.3. Nodeset Numbering**

Nodesets are a critical part of Exodus files. Each nodeset consists of a group of nodes with an associated distribution factor. There is exactly one distribution factor per node in a set. Nodesets are used to apply boundary conditions and to apply loads. Distribution factors are used to provide spatial variation. There are two issues that influence nodeset numbering:

- Because there is only one distribution factor per node, only a scalar can be represented by a single nodeset. Thus, if you wish to apply a force with spatially varying X, Y and Z components, three nodesets are required – one for each component.
- Nodeset numbering must be unique. In NASTRAN, load and BC cards have separate identifiers. Thus, having “FORCE,10,...” and “SPC,10,...” is valid in NASTRAN. To build a consistent Exodus file however, these two cards must be translated into two unique nodesets. In the event that two load or BC cards of the same type share a node the second instance on that node will be deleted and a warning generated.

translating nodesets is done as follows.

1. First the displacement nodesets are processed from SPC type cards. The nodeset ID is constructed from the SID by multiplying by 10 and adding component numbers. Thus,  
`SPC1,30,12,...`  
translates into nodeset ids 301 and 302.
2. Force nodesets are next translated. Each force will generate 3 nodesets. The IDs are computed similarly, but an offset is added so there is no conflict with any displacement nodesets.
3. Moment nodesets are processed exactly like force nodesets. An additional offset is applied.
4. Temperature nodesets are processed exactly like force nodesets. An additional offset is applied.
5. DAREA nodesets are processed exactly like force nodesets. An additional offset is applied.

Information about the nodeset numbering is output during the translation processes. In addition, if Salinas output is requested, further information can be found in the “.inp” file generated.

In addition, translation for Presto may not support some capabilities discussed above. It is advised that the user check the resulting Presto input file for the correct boundary conditions.

## 2.4. Sideset Numbering

Sidesets are collections of element faces that can be used for application of pressure loads. Many codes also use them for application of boundary conditions.

Sidesets are translated from PLOAD1, PLOAD2, and PLOAD4 cards. Only the normal component of pressure is currently translated, i.e. fields greater than 9 on these cards are ignored.

Because Exodus applications use sidesets more extensively than NASTRAN, it may be necessary to “trick” the translator into generating appropriate sidesets. This is done by generating an unreferenced pressure (through a PLOAD card). If the pressure is not referenced in the Bulk Data deck, NASTRAN will ignore it. However, a sideset will be generated within Exodus.

The sideset ID is taken directly from the SID column of the PLOAD\* card (column 2).

As with the nodeset capabilities, Presto translation should be checked for accuracy.

## 2.5. Parameters

Currently, the only PARAM card value used in Presto is `wtmass`. All material densities are multiplied by the value of `wtmass` before being written to the Presto input file. That is, the scaled values of densities are the values that will appear in the material parameters section of the Presto input file. If no PARAM card with `wtmass` is present in the NASTRAN Bulk Data deck, a default value of 1.0 is used.

## 2.6. Functions

NasGen has the ability to translate NASTRAN TABLED1 tables to sierra functions for use in Presto, but only for the LINEAR case. At this time, TABLED2 translation is not supported.

## 2.7. Ground

Some NASTRAN constructs allow attachments to GRID 0, which represents ground. If GRID 0 is referenced in the Bulk Data deck NasGen will generate an additional node at the origin and generate nodeset=1 for that node. This nodeset will need to be fixed in the Salinas and Presto input files.

## 2.8. Case Control

NasGen has limited case control capabilities. Loads and boundary conditions that are present in the NASTRAN database will be translated and used in both the Exodus and Salinas/.inp files. Case control that is recognized includes the following:

solution type (e.g. SOL), SPC, MPC, FREQUENCY, METHOD

This capability is currently not supported for translation to Presto input files.

## 2.9. Element Translation Table

There are two components in the translation of an element (and associated properties) from NASTRAN format to Salinas or Presto. Table 2-2 details the translation of element level data into the Exodus database. This database includes the topology, connectivity and element attributes. In addition, the properties and “behavior” of the element must be represented in the finite element code. Table 2-3 and Table 2-4 contain the element support for Salinas and Presto, respectively. Typically, the Exodus database can be translated with few difficulties. Differences in formulation of the finite elements can cause a significant issue for each element, and elements may lack support due to either NasGen or the finite element code. If an element is not listed in Tables 2-3 or 2-4 it is not supported by Salinas or Presto, respectively. Rigid element support is not reflected in these tables and is discussed in Section 2.9.2.

### Notes from Exodus Translation Table

1. Bar and Beam Attributes are, “area”, “I1”, “I2”, “J”, “orientation(3)”, “offset(3)”. All bar and beam attributes are associated with the entire element, not with the individual ends. No “pin flags” are translated.
2. Dashpot coordinate components are rotated. No support for coupled directions.
3. No support for different component numbers, i.e. C1=C2.
4. Concentrated mass attributes: “mass”, “I11”, “I22”, “I33”, “I21”, “I31”, “I32”, “offset(3)”
5. Coordinates are expanded in Salinas so that each coordinate references only the basic coordinate frame. Currently, this capability is not supported for Presto.
6. Only 8 or 20 node hex elements are supported.
7. Shell attributes include “thickness”, “theta” and “offset”.
8. No support of MCID, TFLAG or thickness variation within the element (an average is used).
9. Tets are supported for 4 and 10 node versions only.
10. Full  $6 \times 6$  stiffness and damping matrices. No support for structural damping or offsets.
11. Limited support.

**Table 2-2.** – NASTRAN/Exodus Translation.

| NASTRAN | Exodus        | Attributes | Notes                |
|---------|---------------|------------|----------------------|
| CBAR    | BEAM          | 10         | <a href="#">1</a>    |
| CBEAM   | BEAM          | 10         | <a href="#">1</a>    |
| CDAMP   | BEAM          | 3          | <a href="#">2</a>    |
| CELAS1  | TRUSS-SPR     | 0          | <a href="#">3</a>    |
| CGAP    | TRUSS-GAP     | 0          | <a href="#">11</a>   |
| CHEXA   | HEX8 OR HEX20 | 0          |                      |
| CONM2   | SPHERE-MASS   | 10         | <a href="#">4</a>    |
| CORD    | CORD          | NA         | <a href="#">5</a>    |
| CPENTA  | WEDGE6 or 15  | 0          | <a href="#">6</a>    |
| CROD    | TRUSS         | “Area”     |                      |
| CQUAD4  | SHELL4        | 3          | <a href="#">7, 8</a> |
| CQUAD8  | SHELL8        | 3          | <a href="#">7, 8</a> |
| CTETRA  | TETRA         | 0          | <a href="#">9</a>    |
| CTRIA3  | TRIANGLE      | 3          | <a href="#">7, 8</a> |
| CTRIA6  | TRIANGLE      | 3          | <a href="#">7, 8</a> |
| CBUSH   | TRUSS-BUS     | 25         | <a href="#">10</a>   |
| CVISC   | TRUS-VIS      | 0          | <a href="#">11</a>   |

**Table 2-3.** – NASTRAN/Salinas Element Support.

| NASTRAN | Salinas            | Issues and Notes     | Status    |
|---------|--------------------|----------------------|-----------|
| CBAR    | Beam2              | <a href="#">b, c</a> | very good |
| CBEAM   | Beam2              | <a href="#">d</a>    | good      |
| CDAMP2  | Dashpot            | <a href="#">e, g</a> | poor      |
| CELAS   | Spring             | <a href="#">f, g</a> | fair      |
| CGAP    | Gap                | <a href="#">h, g</a> | poor      |
| CHEXA   | Hex8 or 20         |                      | excellent |
| CONM2   | Conmass            | <a href="#">i</a>    | excellent |
| CORD    | Coordinate         | <a href="#">j</a>    | very good |
| CPENTA  | Wedge 6 or 15      |                      | very good |
| CROD    | Truss              | <a href="#">g</a>    | very good |
| CQUAD4  | QuadT              | <a href="#">k, l</a> | very good |
| CQUAD8  | Quad8T             | <a href="#">k, l</a> | good      |
| CTETRA  | Tet4 or 10         |                      | excellent |
| CTRIA3  | Tria3 or TriaShell | <a href="#">k, l</a> | very good |
| CTRIA6  | Tria6              | <a href="#">k, l</a> | very good |
| CBUSH   | SpringDashpot      |                      | good      |
| CVISC   | —                  |                      | none      |

**Table 2-4.** – NASTRAN/Presto Element Support.

| NASTRAN | Presto     | Issues and Notes | Status    |
|---------|------------|------------------|-----------|
| CBAR    | Beam       | iii,iv           | good      |
| CBEAM   | Beam       | iii,iv,vi        | good      |
| CHEXA   | Hex 8      |                  | good      |
| CONM2   | Point Mass | v                | very good |
| CPENTA  | Wedge 6    |                  | poor      |
| CQUAD4  | Quad 4     | vii              | good      |
| CTETRA  | Tet 4      |                  | fair      |
| CTRIA3  | Tri 3      | viii             | fair      |

### Notes from Salinas Element Support

- a. Only the topologies listed are supported. For example, there is no 19 node Hex.
- b. There is no variation allowed through the length of the bar.
- c. Torsion of bar elements may be an issue. Some versions of NASTRAN introduce no torsional mass, which allows some solvers to permit torsional degrees of freedom (dofs) to be unattached to the model. Salinas will treat these as zero energy modes.
- d. Beam elements in Salinas are very nearly equivalent to NASTRAN CBAR elements. NASTRAN CBEAM elements are translated to the nearest approximation of these CBAR elements. They have no variation down the length of the bar.
- e. The NASTRAN CDASH element is roughly equivalent to Salinas Dashpots. The scalar damper value, “B”, is stored in the element attributes, but is correct only for an output coordinate system=0. Hand corrections may be needed to the Salinas input.
- f. NASTRAN elements allow almost arbitrary flexibility in the degrees of freedom of CELAS type elements. In particular, stiffness in the X direction can couple to stiffness in the Y direction on the paired node. This flexibility is not fully supported. The Salinas spring elements couple  $X_1$  with  $X_2$ .
- g. One dimensional elements are problematic in parallel applications where it may be impossible to subdivide the model without generating dangling segments.
- h. Gaps are not the same in Salinas and NASTRAN. The Salinas model supports the older NASTRAN gap specification only. Hand tuning is certainly required.
- i. NasGen puts all concentrated masses into block 17 and assigns them a CommassA element type. All properties are read from the Exodus file attributes.
- j. Coordinates are expanded in Salinas so that each coordinate references only the basic coordinate frame.
- k. The NASTRAN and Salinas shell formulations are radically different. Salinas uses a 6 dof/node formulation similar to the DKT membrane for the triangle. Many elements are composites, built of triangles.
- l. TriaShell elements support multiple, orthotropic layers, while the Tria3 does not. If orthotropic layers are identified, then the TriaShell is selected. Likewise, those elements built on triangles (QuadT, Quad8T) select the TriaShell as underlying elements as needed.

## Notes from Presto Element Support

- i. Only the topologies listed are supported. For example, there is no 19 node Hex.
- ii. In general Presto elements differ from NASTRAN elements in that Presto elements are nonlinear, which may cause differences in behavior.
- iii. There is no variation allowed through the length of the bar.
- iv. The moments of inertia and mass in Presto are computed directly from the cross section.
- v. NasGen puts all concentrated masses into block 17 and translates them as point masses. All properties are read from the Exodus file attributes.
- vi. Beam elements in Presto employ a nonlinear formulation and differ significantly from NASTRAN beams. NASTRAN bars and beams are translated to the closest Presto beams.
- vii. The NASTRAN and Presto shell formulations are radically different. Presto employs a 6 dof/node nonlinear formulation.
- viii. Presto does not support multiple orthotropic layers.

### 2.9.1. **Property Cards (PCARDs)**

Translation of properties is very specific to the application code. Tables 2-5 and 2-6 list the translated PCARDs and detail property fields that are partially or completely skipped in translation.

**Table 2-5. – PCARD Translation for Salinas.**

| <b>NASTRAN</b> | <b>partial fields</b> | <b>skipped fields</b>                        |
|----------------|-----------------------|--|
| PBAR           |                       | $C_i D_i E_i F_i K_i$                        |
| PBTRL          |                       | some types                                   |
| PBEAM          | A-end only            | $C_i D_i E_i F_i K_i S_i CW M_i N_i$         |
| PBEAML         | A-end only            | some types. $SO_i$                           |
| PCOMP          |                       | SB FT TREF GE LAM SOUTi                      |
| PELAS          |                       | GEi Si                                       |
| PGAP           |                       | MU1 MU2 TMAX MAR TRMIN                       |
| PSHELL         |                       | 12I/T <sup>3</sup> MID2 MID3 TS/T Z1 Z2 MID4 |
| PSOLID         |                       | IN STRESS ISOP FCTN                          |
| PROD           |                       | J C  |

**Table 2-6. – PCARD Translation for Presto.**

| <b>NASTRAN</b> | <b>partial fields</b> | <b>skipped fields</b>                                      |
|----------------|-----------------------|--|
| PBTRL          | TYPE                  | some types GROUP NSM                                       |
| PBEAML         | TYPE A-end only       | some types NSM <sub>i</sub> SO <sub>i</sub> X <sub>i</sub> |
| PSHELL         |                       | 12I/T <sup>3</sup> MID2 MID3 TS/T Z1 Z2 MID4 NSM           |
| PSOLID         |                       | CORDM IN STRESS ISOP FCTN                                  |

## 2.9.2. *Rigid Pseudo Element*

NASTRAN contains a rich set of rigid elements that are essential to structural analysis. The main features of these rigid elements are translated by NasGen and are available within Salinas and, to a lesser extent, Presto. There are some significant differences that are outlined below. All such rigid elements depend on selection criteria for the dependent and independent degrees of freedom. In NASTRAN, these decisions are explicitly specified in the input. Salinas and Presto compute these sets as described below.

### **Salinas Rigid Element Limitations**

**RROD** translates into a beam for visualization. Each beam constrains 1 DOF.

**RBAR** translates into a beam for visualization. The number of constraint equations depends on the coordinate mask (Section 2.9.2.1).

**RTRPLT** translates into 3 RBAR type elements.

**RBE1** does not translate.

**RBE2** translates into a collection of RBAR elements. The number of constraint equations depends on the coordinate mask (Section 2.9.2.1).

**RBE3** translates into a collection of beams. Each RBE3 generates a new element block.

### **Presto Rigid Element Limitations**

NasGen translation for Presto handles all rigid RBAR, RROD, RTRPLT and RBE2 elements together, sorting out which rigid elements form separate rigid bodies. The rigid elements are written to a single element block while the separate rigid bodies are distinguished by an attribute value written on the rigid elements in the Exodus file. Presto reads this attribute and treats the corresponding elements as rigid bodies. RBE3 elements are different and translate to MPCs for Presto (though with only partial support).

**RBAR** translates into a beam for visualization. Each beam constrains 6 DOFs.

**RROD** translates into a collection of RBAR elements. (Each RBAR constrains 6 DOFs.)

**RTRPLT** translates into a collection of RBAR elements. (Each RBAR constrains 6 DOFs.)

**RBE2** Fully constrained RBE2 (those that constrain all six DOFs) translates into a collection of RBAR elements. (Each RBAR constrains 6 DOFs.) Partially constrained RBE translate into an MPC with one independent node and the remaining nodes dependent.

**RBE3** translates to an MPC based on the first independent-dependent set of nodes in the RBE3. A collection of beams is also written to the Exodus file for visualization, but the block containing these bars is omitted in the Presto input file (since the MPC is the translation of the RBE3 element).

## Presto PCOMP Limitations

Presto does not support a composite shell capability. The PCOMP card is translated to be a layered shell capability. Currently, there is no support for various fiber orientations per layer or any material other than elastic. This is a limited capability and should be used carefully since Presto and Salinas do not offer the same capabilities with respect to this card.

### 2.9.2.1. Coordinate Mask

NASTRAN input employs a coordinate mask on some fields. For example, the fourth field of an RBE2 describes the coordinate degrees of freedom which are active for the dependent nodes of that pseudo-element.

Early versions of NASGEN did not parse that field, but constrained all the structural degrees of freedom associated with the nodes. Current code <sup>1</sup> stores information in the exodus element attributes that are used to restrict the constraint equations applied. Because Exodus attributes are always stored as real numbers, the NASTRAN coordinate mask is mapped to a real number representative of the active dofs. The position in the exodus mask is significant. There are two attributes associated with each element which refer to the nodes on each end.

Defining  $\gamma(x)$  to be 1 if dof  $x$  is active, and 0 otherwise, the exodus attribute is set as follows,

$$mask = 100000\gamma(x) + 20000\gamma(y) + 3000\gamma(z) + 400\gamma(R_x) + 50\gamma(R_z) + 6\gamma(R_z)$$

Thus,  $mask = 123456$  when all dofs are active, and 123000 if only translations are active.

## 2.10. Recognized BDF cards

The following cards are at least partially recognized in the NasGen translator.

CBAR, CBEAM, CBUSH, CDAMP, CELAS1, CELAS2, CHEXA, CONM2, CORD2C, CORD2R, CORD2S, CPENTA, CQUAD4, CQUAD8, CROD, CTETRA, CTRIA3, CTRIA6, DAREA, FORCE, FORCE1, FORCE2, FREQ1, FREQ2 GRID, MPC, MPCADD, MAT1, MAT8, MOMENT, MOMENT1, MOMENT2, PBAR, PBARL\*, PBEAM, PBUSH, PCOMP, PDAMP, PGAP, PARAM, PLOAD, PSHELL, PSOLID, RBAR, RBE1, RBE2, RBE3, RROD, RTRPLT, SPC, SPC1, SPCD, TABLE

---

<sup>1</sup>Revisions as of 2/2011 or later.

## **2.10.1. Additional Salinas BDF Card Support Details**

**CHEX** Only CHEX elements with 8 or 20 grid points are supported.

**CONM2** CONM2 cards with a CID not equal to 0 are not well tested. The values of the mass moments of inertia exported to Exodus should be examined to ensure that they were translated correctly.

**CORDiC CORDiR CORDiS** All coordinate systems are fully supported, but the frames are not nested. Each frame is redefined in terms of the basic frame.

**CPENTA** Only CPENTA elements with 6 or 15 grid points are supported.

**CQUAD** Only CQUAD elements with 4 or 8 grid points are supported.

**CQUAD4 CQUAD8** The element thickness exported to Exodus is an average of T1-T4. If any thickness is blank, then it is replaced with T1. If thickness is not specified, then the value of the associated PSHELL card is used. THETA and MCID are ignored.

**CQUADR CQUADX** Not supported.

**CROD** Fully supported.

**CTETRA** Only CTETRA elements with 4 or 10 grid points are supported.

**CTRIA3 CTRIA6** The element thickness exported to Exodus is an average of T1-T3. Blank thicknesses are replaced with T1. The default thickness is the thickness of the associated PSHELL card is used. THETA and MCID are ignored.

**CTRIAR CTRIAX** Not supported.

**FORCE FORCE1 FORCE2** Fully supported

**GRID** Permanent single-point constraints are not supported. An SPC1 card must be used instead. If a GRID card with single-point constraints is present, then a warning will be generated.

**MOMENT MOMENT1 MOMENT2** Fully supported.

**PBAR** A, I1, and I2 used. All other fields ignored.

**PBARL** A few of the more common cross sections are converted to equivalent PBAR terms (A, I1, I2).

**PBEAM** A, I1, and I2 used. All other fields ignored.

**PLOAD1** PLOAD2 PLOAD4 PLOAD1 cards with moment load types are treated as force load types and a warning is generated. PLOAD1 cards are not well tested; they should be checked after translation. PLOAD2 and PLOAD4 cards fully supported, including cards defined with “Thru” field.

**PROD** A used, all other fields ignored.

**PSHELL** T used, all other fields ignored.

**PSOLID** Ignored.

**RBAR RROD RTRPLT** All elements are assigned to one Exodus element block. Limited support.

**RBE1** Not supported.

**RBE2 RBE3** Each element is assigned to its own Exodus element block. Limited support.

**SPC SPC1 SPCD** Fully supported. A nodeset per degree of freedom is generated for each constraint set.

## 3. NASGEN SUPPORT

### 3.1. Known Deficiencies

The following deficiencies exist in the code at the time of this writing.

**Sidesets:** Processing of sidesets on element edges has not yet been completed. At this point, it is recommended that these be added later by hand if necessary using a tool such as p3/exodus.

**element offsets:** Offsets for beam elements are translated from the values at one end, i.e. the offsets at each end are assumed to be identical and are taken from BDF fields 14-16 of the CBEAM card.

**permanent constraints:** Constraints introduced on the GRID BDF card are currently ignored.

**TLoads:** Time dependent loads are not currently translated.

**parameters:** Most NASTRAN parameters are not read or translated. The Exodus file would not normally depend on these.

**uppercase:** Translation of lowercase BDF files has not been thoroughly tested. Convert them to uppercase first.

**Limited BDF format:** Most test cases have been run using the small BDF format (i.e. 8 characters/field). In a few cases the large format has been used, but it is not extensively tested. The free form (comma delimited) field format is also not well tested.

**Free form continuations:** Continuation cards using the free form format (comma delimited) are not well tested. The blank delimited free field format is not supported.

**Free form truncation:** Free format fields are *truncated* at 8 characters, rather than rounding.

**Replication:** Replication, in either fixed or free field formats, is not supported.

**arbitrary continuations** Only continuation cards immediately following the parent cards are supported.

There are many BDF cards that are not translated by this translator. These can usually be determined using the “-u” option, which will attempt to list cards that were not translated to the Exodus or input files (or both). In addition, many cards are only partly translated. For example, pin information on beam cards is silently ignored. *It is critical that the analyst inspect the resulting translation to ensure that it is complete for his application.*

### **3.2. Support**

Nasgen is provided to assist in the migration of structural models from NASTRAN to Exodus formats. The Sierra Structural Dynamics and Solid Mechanics Team will try to fix bugs as they are found. Send bug reports and issues to [sierra-help@sandia.gov](mailto:sierra-help@sandia.gov). Clearly identify the program (NasGen) and if possible, include an example BDF file fragment.

### **3.3. Pedigree**

NasGen grew out of a previous translator, `pat2exo`, which generated an Exodus file from a patran neutral file. Richard Naething wrote the core elements of NasGen during the summer of 2001. Additional work and functionality was added by Garth Reese in early 2002, and Richard Naething during the summer of 2002. Extensive additions were made in 2009 and 2010 by the Sierra Structural Dynamics and Solid Mechanics Team.<sup>1</sup>

## BIBLIOGRAPHY

- [1] Edward A. Bourcheron et al. *Sandia National Laboratories Advanced Simulation and Computing (ASC) Software Quality Plan Part 1: ASC Software Quality Engineering Practices Version 1.0*. Tech. rep. SAND2004-6602. PO Box 5800, Albuquerque, NM 87185-5800: Sandia National Laboratories, 2005 (cit. on p. 28).
- [2] F. Fuentes et al. “Orientation embedded high order shape functions for the exact sequence elements of all shapes”. In: *Computers and Mathematics with Applications* 70.1 (2015), pp. 353–458 (cit. on p. 12).

## DISTRIBUTION

### Email—Internal

| Name              | Org. | Sandia Email Address |
|-------------------|------|----------------------|
| Technical Library | 1911 | sanddocs@sandia.gov  |

### Hardcopy—Internal

| Number of Copies | Name          | Org. | Mailstop |
|------------------|---------------|------|----------|
| 1                | K. H. Pierson | 1542 | 0845     |





**Sandia  
National  
Laboratories**

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology & Engineering Solutions of Sandia LLC, a wholly owned subsidiary of Honeywell International Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.