


3-year | \$2.79M in funding from the U.S. Dept. of Energy

Objective

Develop the ENDURING system and components for long-duration energy storage (LDES) capable of **10–100 hours** storage duration, **50–400 MWe** power capacity.

Significance

- Potential to achieve **grid-scale energy storage** at a fraction of the cost of conventional chemical battery technologies.
- The ability to provide **base-load power for several days** allows for continued grid integration of intermittent renewable sources.



Dr. Scott Litzelman
Dr. Vivien Lecoustre
Mr. Max Tuttmann



Dr. Zhiwen Ma (PI)
Mr. Patrick Davenport
Dr. Jacob Wrubel
Dr. Janna Martinek



Prof. Ruichong Zhang
Dr. Xingchao Wang
Mr. Jeffery Gifford



Prof. Aaron Morris
Mr. Jason Schirck



Dr. James Tallman
Dr. Doug Hofer
Mr. Vitali Lissianski



Mr. Matt Lambert

System Overview



1. Particle lifting by skip hoist.



2. Electric particle heater for *charging*.

- Load following capability.



3. Thermal energy storage (TES) at 1,200°C.

- 900°C ΔT increases storage density.
- Silica sand at \$30-40/ton.
- Low-cost containment.
- Storage cost of ~\$2/kWh_t.




4. Discharging Fluidized bed heat exchanger.

- Direct particle/gas contact.

5. Power generation

- GE 7E.03 combined cycle




Scalable for 0.5- 80 GWh_t storage, 50-400 MW_e generation



Material/Prototype Development and Testing



Screened and tested materials




Testing charging heater and storage prototype



Testing cold/hot prototypes for discharging heat exchanger



Product fluidized bed heat exchanger design



Working with industry partners on components and system

Remaining gaps, challenges, and R&D

- Four patent applications are filed on component and system designs.
- The ENDURING thermal energy storage can be initially deployed on an existing thermal power plant.
- **Need pilot demonstration at 1–5 MW scale to verify commercial potentials:**
 - Develop product-relevant prototype design, fabrication, and operation for charging heater, fluidized-bed heat exchanger, particle handling, and TES containment.
 - A 60-meter-tall particle lift structure near NREL can be a test site for the pilot demonstration.



Seek partner and support to develop pilot and product path.